

## Legno Pflegeöl

7009

Universal **after-care oil** for furniture and interior finishing for use in **DIY and trade**

### PRODUCT DESCRIPTION

#### General

Fast-drying, easy to use after-care oil for treating both hardwoods and softwoods. To clean and freshen up oiled surfaces with light soiling and restore their pleasant feel. Antistatic. Hardening is achieved by absorption of oxygen from the atmosphere (oxidative drying).

#### Special properties and standards



- **DIN 53160-1 and DIN 53160-2**  
Perspiration and saliva-proof properties



- **ÖNORM EN 71-3**  
Safety of toys; migration of certain elements (free of heavy metals)



- **Food-compatible coating**  
The product can be used for coatings of wooden objects that temporarily come in contact with foodstuffs, according to confirmation of OFI Technologie & Innovation GmbH.



- **French ordinance DEVL1104875A**  
Marking of construction coating products for their emission of volatile pollutants: A+

#### Application area



For surface treatment of surfaces in furniture and interior finishing that are subject to a normal level of wear, e.g. bedroom and living room fittings, as well as wooden floors.

Apply a maximum of one thin coat of this product to the inner surfaces of furniture and cabinets on account of possible odours.

#### Substances contained

Modified vegetable oils, waxes, matting agents, solvents that are free from aromatic hydrocarbons, lead-free and cobalt-free drying agents.

### PROCESSING

#### Processing instructions



- Please stir and shake the product well before use.
- The product is ready to use.
- The temperature of the product and object, and the room temperature must be at least +10 C.

- The optimal conditions for use are between 20 - 25 °C with a relative atmospheric humidity between 40 - 60 %.
- Apply the product and leave a short time to take effect and then carefully wipe of the excess with a cotton cloth or pack of gauze in the direction of the fibre.
- Two applications may be needed for surfaces that have been subjected to heavy usage.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please read and take note of our working guidelines **ARL 013 – Safety measures required for the use of oils and waxes that dry by oxidation** and **ARL 160 – Working guidelines for oils and waxes**.

### Application technique



	<b>Wiping</b>
<b>Yield per application (m<sup>2</sup>/l)</b>	15 - 30

The shape and surface condition of the workpiece as well as the type of application influence the actual consumption. Accurate values for consumption must be obtained by applying trial coats in advance.

### Drying times

(at 23 °C and 50 % rel. humidity)



Follow-up treatment	4 hour(s)
Thoroughly dried	7 day(s)

The figures given above are reference values. Drying depends on the substrate, layer thickness, temperature, air exchange, relative humidity, stacking pressure and stacking conditions.

To ensure perfect drying, good room ventilation must be provided. Low ventilation, e.g. from dense stacking, delays drying.

Lower temperatures and/or high level of atmospheric humidity can increase the drying time.

On types of woods rich in extracts (such as oak, iroko), drying may be delayed.

## SUBSTRATE

### Type of substrate

Oiled hardwoods and softwoods

### Substrate property

The substrate must be dry, clean, capable of holding the paint, free from separating substances such as grease, wax, silicone, resin etc. and free from wood dust, as well as tested for suitability for coating.

## PROCESSING STEPS

### Product application

1 x Legno Pflegeöl (7009)

## CLEANING AND MAINTENANCE

### Cleaning

**Clean** with water, Clean-Möbelreiniger (7202), Clean-Parkettreiniger (7207) or a mild household cleaner. Use Legno Reiniger (7003) for greasy stains.

Cleaning must be carried out at the earliest 14 days after application of the oil/wax/hard wax oil.

Abrasive cleaning agents should not be used.

<b>Maintenance</b>	Please read and take note of our <b>ARL 252 – Care instructions for floors treated with Legno-Öl or Legno-Color</b> , <b>ARL 254 – Care instructions for furniture treated with Legno-Öl or Legno-Color</b> .
--------------------	---

## ORDERING INFORMATION

<b>Size of trading unit</b>	250 ml, 1l
-----------------------------	------------

<b>Colour shades</b>	Legno-Pflegeöl (7009000210)
----------------------	-----------------------------

<b>Supplementary products</b>	Clean-Möbelreiniger (7202) Clean-Parkettreiniger (7207) Legno Reiniger (7003) Please refer to the corresponding technical data sheets of the products.
-------------------------------	---

## FURTHER DETAILS

### Durability / storage



Min. 1 year(s) in the original sealed containers.

With containers under 3 kg the shelf life is 3 year(s).

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

We recommend to transfer the contents of open containers to smaller ones in order to prevent gelling / skin formation.

<b>Giscode</b>	Ö60
----------------	-----

### Safety information



Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at [www.adler-lacke.com](http://www.adler-lacke.com).